



TECTALOY MUKOWT RADIATOR FLUSH

INTRODUCTION

Tectaloy Mukowt is an ideal cooling system cleaner and pre-conditioner designed for use prior to filling with your preferred Tectaloy Coolant or Corrosion Inhibitor. It is suitable for use with all radiator cooling systems.

TYPICAL APPLICATIONS

Recommended between flushes to clean and pre-condition vehicle cooling system.

ADVANTAGES

- Gentle action alkaline solution.
- Effectively removes oil and sludge.
- Safe to use with all alloys.
- Fast acting formula.

SPECIFICATIONS

- Cooling system cleaner.
- Ready to use.
- Alkaline based.

Turn over for usage directions



FAST ACTING FORMULA

READY TO USE

ALKALINE BASED

Product Code	Size	Product Barcode	Ctn. Qty.	Carton Barcode
TE610	500mL	9312924006008	12	19312924006005

ABN 63 004 235 063

PH: 1800 177 989 or E: sales@aamtech.com.au

1-9 Nina Link, Dandenong South, VIC 3175

www.aamtech.com.au

ITW AAMTECH
Automotive AfterMarket Technologies



DIRECTIONS FOR USE

TECTALOY PLUS - MUKOWT RADIATOR FLUSH

Product Code	Size	Colour
TE610	500ml	-

DIRECTIONS FOR USE:

1. Drain cooling system of all coolant
2. Refill with clean soft or demineralised water
3. Add 500ml of Mukowt for every 10 litres of water
4. Run engine for minimum of 20 minutes. For extremely dirty cooling systems increase running time to several hours and repeat flushing procedure until clean
5. Flush out cooling system with clean, soft or demineralised water
6. Fill with the correct Tectaloy coolant to suit your vehicle

ABN 63 004 235 063

PH: 1800 177 989 or E: sales@aamtech.com.au

1-9 Nina Link, Dandenong South, VIC 3175

www.aamtech.com.au

 **AAMTECH**
Automotive AfterMarket Technologies