

TECTALOY®

60 PLUS

TECTALOY 60 PLUS GENERAL PURPOSE

INTRODUCTION

Tectaloy 60 Plus is a conventional pre-mixed radiator coolant designed for general purpose use. Formulated to protect against overheating, aluminum corrosion, general rust & heat transfer loss and rubber hose breakdown.

TYPICAL APPLICATIONS

60 Plus is designed to meet the demands of normal passenger vehicles under light to normal driving conditions.

ADVANTAGES

- Ready to Use.
- 4 Years or 120,000km.
- -2°C Anti-Freeze Protection.
- +122°C Anti Boil Protection.
- 100% Corrosion protection when used as directed.
- Silicate, phosphate & amine free.

SPECIFICATIONS

- Conventional.
- Contains ethylene glycol 65g/Litre.
- Exceeds Australian Standard AS2018-2004.

Turn over for usage directions.



READY TO USE

4 YEARS OR 120,000 KMS

ANTI FREEZE/ANTI BOIL

Colour	Product Code	Size	Product Barcode	Ctn. Qty.	Carton Barcode
Green	T60PG1L	1L	9312924007234	6	69312924007236
	T60PG5L	5L	9312924007241	3	39312924007242

ABN 63 004 235 063

PH: 1800 177 989 or E: sales@aamtech.com.au

1-9 Nina Link, Dandenong South, VIC 3175

www.aamtech.com.au

ITW AAMTECH
Automotive AfterMarket Technologies



DIRECTIONS FOR USE

TECTALOY 60 PLUS - GENERAL PURPOSE COOLANT

Product Code	Size	Colour
T60PG1L	1L	Green
T60PG5L	5L	

DIRECTIONS FOR USE:

1. Refer to the owners manual for cooling system capacity
2. Drain cooling systems and flush with clean soft or demineralised water
3. For best results use Tectaloy Plus Mukowt Radiator Flush
4. Add the required amount of Tectaloy 60 Plus, do not add water
5. Run the engine, bleed the cooling system correctly, ensuring the thermostat is open and check level when cool
6. Maximum useful life of 4 years or 120,000km when used as recommended

Do not mix coolants

ABN 63 004 235 063

PH: 1800 177 989 or **E:** sales@aamtech.com.au
1-9 Nina Link, Dandenong South, VIC 3175
www.aamtech.com.au

ITW AAMTECH
Automotive AfterMarket Technologies