

# TECTALOY®

## UNLMTD

## TECTALOY UNLMTD READY TO USE PRE-MIX

### INTRODUCTION

Tectaloy Unlmtd Ready to Use Pre-Mix is an Organic Acid Technology (OAT) radiator coolant, pre-mixed to 33% glycol concentrate. This is the perfect choice of coolant for applications where an extra load is placed on the engine.

### TYPICAL APPLICATIONS

Tectaloy Unlmtd Ready to Use Pre-Mix is designed to meet the everyday demands of petrol and diesel vehicles. Its unique formula allows extra cooling system protection when required, such as four-wheel driving, towing heavy trailers or caravans.

### ADVANTAGES

- Ready to Use.
- 10 Years or 1,000,000km.
- -19°C Anti-Freeze Protection.
- +125°C Anti Boil Protection.
- 100% Corrosion protection when used as directed.
- An excellent choice for high-performance multi-valve engines.

### SPECIFICATIONS

- Contains 33% ethylene glycol.
- Type A Coolant.
- OAT corrosion inhibitors.
- Silicate, phosphate & amine free.
- Available in Green, Red and Blue to suit your OEM requirements
- Exceeds Australian Standards AS2108-2004

Turn over for usage directions



**READY TO USE**

**10 YRS OR 1,000,000 KMS**

**CORROSION PROTECTION**

Colour	Product Code	Size	Product Barcode	Ctn. Qty.	Carton Barcode
Green	TUPG1L	1L	9312924007302	6	69312924007304
	TUPG5L	5L	9312924007326	3	39312924007327
	TUPG20L	20L	9312924007319	EACH	-
Red	TUPR1L	1L	9312924007333	6	69312924007335
	TUPR5L	5L	9312924007340	3	39312924007341
Blue	TUPB5L	5L	9312924007296	3	39312924007297

ABN 63 004 235 063

PH: 1800 177 989 or E: sales@aamtech.com.au

1-9 Nina Link, Dandenong South, VIC 3175

www.aamtech.com.au

**ITW AAMTECH**  
Automotive AfterMarket Technologies



## DIRECTIONS FOR USE

### TECTALOY UNLMTD - READY TO USE PRE-MIX

Product Code	Size	Colour
TUPG1L	1L	Green
TUPG5L	5L	
TUPG20L	20L	
TUPR1L	1L	Red
TUPR5L	5L	
TUPB5L	5L	Blue

#### DIRECTIONS FOR USE:

1. Refer to the owners manual for cooling system capacity
2. Drain cooling systems and flush with clean soft or demineralised water
3. For best results use Tectaloy Plus Mukowt Radiator Flush
4. Add the required amount of Tectaloy Unlmtd Ready to Use Pre-Mix, do not add water
5. Run the engine, bleed the cooling system correctly, ensuring the thermostat is open and check level when cool
6. Maximum useful life of 10 years or 1,000,000km when used as recommended

Do not mix coolants

**ABN 63 004 235 063**

**PH:** 1800 177 989 or **E:** sales@aamtech.com.au

1-9 Nina Link, Dandenong South, VIC 3175

www.aamtech.com.au

**ITW AAMTECH**  
Automotive AfterMarket Technologies