

DIRECTIONS FOR USE



TECTALOY PLUS - XTRA COOL GOLD CORROSION INHIBITOR CONCENTRATE

Product Code	Size	Colour
TEXG1L	1 Litre	Green
TEXG20L	20 Litres	Green
TEXGR1L	1 Litre	Red
TEXGR20L	20 Litres	Red

DIRECTIONS FOR USE:

1. Refer to the vehicle owners manual for cooling system capacity
2. Drain cooling system and flush with clean soft or demineralised water
3. Use Tectaloy Mukowt if the cooling system is dirty
4. Add Tectaloy Xtra Cool Gold to the radiator at the correct dose rate and then refill the radiator with clean, soft or demineralised water. Do not over dilute as this will adversely affect the performance of the product
5. Run the engine, bleed the cooling system correctly, ensuring the thermostat and heating circuit is open and check the level when cool

Replace every 3 years or 100,000km when using soft or demineralised water (60,000 km if using clean soft water). Avoid mixing with other coolants as this may affect coolant performance. If spilt on paintwork wash off with water immediately. Used coolants may harm the environment. Dispose of as directed by the EPA. Store in a sealed container out of direct sunlight.

TECTALOY PLUS - XTRA COOL CORROSION INHIBITOR CONCENTRATE

Product Code	Size	Colour
TEX500	500ml	Green
TEX20L	20 Litres	Green

DIRECTIONS FOR USE:

1. Refer to the vehicle owners manual for cooling system capacity
2. Drain cooling system and flush with clean soft or demineralised water
3. Use Tectaloy Mukowt if the cooling system is dirty
4. Add Tectaloy Xtra Cool to the radiator at the correct dose rate and then refill the radiator with clean, soft or demineralised water. Do not over dilute as this will adversely affect the performance of the product
5. Run the engine, bleed the cooling system correctly, ensuring the thermostat and heating circuit is open and check the level when cool
6. Replace every 2 years or 40,000km when using clean soft or demineralised water

Avoid mixing with other coolants as this may affect coolant performance. If spilt on paintwork wash off with water immediately. Used coolants may harm the environment. Dispose of as directed by the EPA. Store in a sealed container out of direct sunlight.