



TECTALOY PLUS HD2 RADIATOR FLUSH

INTRODUCTION

Tectaloy HD2 Heavy Duty Radiator Flush is a professional strength cooling system cleaner designed to clean and condition very dirty systems that require thorough flushing. prior to filling with high quality Tectaloy coolants.

TYPICAL APPLICATIONS

Recommended between flushes to clean and pre-condition vehicle cooling system

ADVANTAGES

- Assists in removal of rust and scale.
- Effectively removes oil and sludge.
- Safe to use with all alloys.

SPECIFICATIONS

- Heavy duty formula.
- Ready to use.
- Acid based.
- Recommended to prepare cooling systems where an organic based coolant or inhibitor is to be used.

Turn over for usage directions



HEAVY DUTY FORMULA

REMOVES OIL AND SLUDGE

READY TO USE

Product Code	Size	Product Barcode	Ctn. Qty.	Carton Barcode
TEHD21L	1L	9312924007005	6	19312924007002

ABN 63 004 235 063

PH: 1800 177 989 or E: sales@aamtech.com.au
1-9 Nina Link, Dandenong South, VIC 3175
www.aamtech.com.au

ITW AAMTECH
Automotive AfterMarket Technologies



DIRECTIONS FOR USE

TECTALOY PLUS HD2 HEAVY DUTY RADIATOR FLUSH

Product Code	Size	Colour
TEHD21L	1L	-

DIRECTIONS FOR USE:

1. Drain cooling system of old coolant. Seal cooling system and add HD2 Heavy Duty Radiator Flush
2. Refill system with clean, soft or demineralised water
3. Open heater circuit and run engine at a fast idle for 15 minutes. A maximum run time of two hours should not be exceeded
4. When cool, drain the cooling system and flush thoroughly with clean, soft or demineralised water, repeat until clean
5. The cooling system is now ready for an addition of a suitable Tectaloy Coolant

ABN 63 004 235 063

PH: 1800 177 989 or E: sales@aamtech.com.au
1-9 Nina Link, Dandenong South, VIC 3175
www.aamtech.com.au

 **AAMTECH**
Automotive AfterMarket Technologies