

# DIRECTIONS FOR USE



## TECTALOY UNLMTD - CONCENTRATE COOLANTS

Product Code	Size	Colour
TUG1L	1L	Green
TUG5L	5L	
TUG20L	20L	
TUR5L	5L	Red
TUR20L	20L	
TUB5L	5L	Blue

### DIRECTIONS FOR USE:

1. Start with a cool engine. Remove the radiator cap.
2. Place a container under the drain plug. Open the plug & drain coolant completely.
3. Close the drain plug and refill the radiator with soft or demineralised clean water. Leave the radiator cap off.
4. Run the engine with the heater set on HOT for at least 2-5 minutes (ensuring the thermostat is open).
5. Repeat steps 2-4 until water drained is clear with no coolant visible.  
TIP: For best results use Tectaloy Plus Mukowt Radiator Flush, as per the directions on the pack.
6. Drain the radiator again and close the drain plug.
7. Add Tectaloy UnlmtD Concentrate coolant at the correct dose rate and then fill radiator, using either soft potable water or preferably demineralised clean water
8. Follow air-bleeding procedures as per vehicle manufacturer's instructions.
9. Re-run the engine with the heater ON (ensuring the thermostat is open), so the coolant circulates.
10. Top up as necessary. Reinstall the radiator cap.

## TECTALOY UNLMTD - READY TO USE PRE-MIX

Product Code	Size	Colour
TUPG1L	1L	Green
TUPG5L	5L	
TUPG20L	20L	
TUPR1L	1L	Red
TUPR5L	5L	
TUPB5L	5L	Blue

### DIRECTIONS FOR USE:

1. Refer to the owners manual for cooling system capacity
2. Drain cooling systems and flush with clean soft or demineralised water
3. For best results use Tectaloy Plus Mukowt Radiator Flush
4. Add the required amount of Tectaloy UnlmtD Ready to Use Pre-Mix, do not add water
5. Run the engine, bleed the cooling system correctly, ensuring the thermostat is open and check level when cool
6. Maximum useful life of 10 years or 1,000,000km when used as recommended

Do not mix coolants